



Greases

# Eurol PTFE Complex Grease EP 2

Lithium complex with PTFE for a wide application range

## Description

Eurol PTFE Complex Grease EP 2 is based on the well known Eurol Lithium Complex Grease. A percentage PTFE (poly tetra fluor ethylene) is added to this grease, so Eurol PTFE Complex Grease EP 2 offers an even better lubricity.

Eurol PTFE Complex Grease EP 2 is successfully applied in a wide range of applications, operating in a temperature range of -30°C up to +170°C. It is recommended to shorten re-lubrication intervals, if temperatures exceed 200°C.

Eurol PTFE Complex Grease EP 2 is extremely suitable as a 'life-time' lubricant for heavily loaded wheel bearings of trucks, electro motors and kiln bearings. Due to the excellent sealing properties, penetration of dust, dirt and water in the bearing is avoided.

## Performance level

- DIN 51825: KPF2N-30
- ISO-L-XCDIB2

## Physical properties

Colour	white	
Density at 20°C	0.91 kg/l	ASTM D 4052
NLGI consistency	2	
Thickener type	Lithium	
Base oil type	Mineral	
Base oil viscosity	210 cSt	ASTM D 445
4-ball weld load	300 kg	ASTM D 2596
Operating temperature	-30 – 140 °C	
Dropping point	270 °C	

Article number E901280  
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.