



Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C PSC

Silicate free long-life coolant for PSA B71 5110

Beschreibung

Eurol Coolant -36°C PSC has especially been developed for the cooling systems according to modern engine requirements of the Peugeot & Citroën car manufacturers.

Eurol Coolant -36°C PSC is an ethylene glycol based coolant that provides long-life corrosion protection by the use of special corrosion inhibitors for engine manufactured cooling systems from cast iron, aluminium or combinations of the two metals.

Eurol Coolant -36°C PSC prevents from scale formation, foam-building, sludge formation and leakage. The product does not affect rubber, plastics, metals, aluminum or its alloys.

Eurol Coolant -36°C PSC can be used in all cooling systems made of aluminium and ferrous alloys.

Eurol Coolant -36°C PSC provides a permanent, guaranteed protection against freezing up to -36 °C and has to be used undiluted. Never top-up with water.

Eurol Coolant -36°C PSC is silicate, amine, borate, nitrite and phosphate free.

Eurol Coolant -36°C PSC is compatible with most other coolants based on silicate free ethylene glycol. However, an exclusive use of Eurol Coolant -36°C PSC is strongly recommended for optimum corrosion protection and sludge control.

Performance level

- PSA B71 5110

Physikalische Eigenschaften

Farbe	Blau	
Dichte bei 20°C	1.07 kg/L	ASTM D 4052
Frostschutz	-36 °C	ASTM D 1177
pH-Wert	8.5	

Artikelnummer E504014
Version 1.0, 12-12-2018

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.