



Motorcycle oils 4T - Mineral

## Eurol 4T Road 10W-50

Mineral motor oil for 4-stroke motorcycles

### Description

Eurol 4T Road 10W-50 is a mineral engine oil without friction modifiers and has been especially developed for 4-stroke motorcycles. This oil can also be used in motorcycle transmissions where an API SG oil is prescribed.

Eurol 4T Road 10W-50 is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol 4T Road 10W-50 offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised.

Eurol 4T Road 10W-50 has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

### Performance level

- API SJ
- JASO MA
- JASO MA2

### Physical properties

Colour	amber	
Density at 20°C	0.86 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	121.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	17.4 cSt	ASTM D 445
Viscosity Index	158	ASTM D 2270
Viscosity, dynamic (CCS)	6432 cP	ASTM D 5293
Flash point	214 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

Article number E100100  
Version 1.2, 29-10-2019

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.