



Heavy duty diesel engine oils - Mineral

## Eurol Bediga 15W-40

Mineral motor oil for mixed fleet

### Description

Eurol Bediga 15W-40 is an engine oil providing an optimum lubrication for older passenger cars and light loaded commercial vehicles equipped with gasoline, LPG and diesel engines.

Eurol Bediga 15W-40 is suitable for turbo charged engines, multi-valve technology and engines with catalytic converters.

Eurol Bediga 15W-40 offers excellent wear protection to all engine parts. These parts will also be protected against rust and corrosion. Special deterging additives keep rust particles and soot in dispersion. Eurol Bediga 15W-40 also contains special additives to prevent from oil thickening caused by oxidation at high temperatures.

Due to the use of shear stable viscosity index improves the viscosity will stay in grade, so that also during long drain interval terms, Euro Bediga 15W-40 will continue to provide a strong lubricant film between the moving parts of the engine.

### Performance level

- API SG/CF-4

### Recommended for use

- MIL-L-2104D
- MIL-L-46152

### Physical properties

Colour	brown	
Density at 20°C	0.866 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	105.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.7 cSt	ASTM D 445
Viscosity Index	143	ASTM D 2270
Viscosity, dynamic (CCS)	4734 cP	ASTM D 5293
Base number	11.9 mg	ASTM D 2896
Sulphated ash	1.6 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E100125  
Version 3.0, 15-03-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.