



Nautic line - Mineral

Eurol Nautic L.10W-30 FCW

4 stroke oil for outboard motors

Description

Eurol Nautic Line 10W-30 FCW is a motor oil that ensures an optimal lubrication and protection of 4 stroke outboard motors.

Eurol Nautic Line 10W-30 FCW fulfils the NMMA FCW requirements, such as protection against rust and corrosion through contact with (salt) water, a limited decrease in viscosity after long-term use and an excellent protection against wear and sedimentation, especially in case of fuel dilution*.

*Fuel dilution can happen in outboard motors, when the motor runs for an extended time in neutral, and unburnt fuel leaks into the crankcase. Eurol Nautic Line 10W-30 FCW contains special additives that limit wear to a minimum both at low and high speeds.

Thanks to special additives, Eurol Nautic Line 10W-30 FCW will keep providing its high performance level even after the oil change term has passed. However, it is always best to ensure timely oil changes.

Performance level

- API SL
- JASO MA
- NMMA FC-W

Physical properties

i ilysicai properties		
Colour	brown	
Density at 20°C	0.864 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	77 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.8 cSt	ASTM D 445
Viscosity Index	148	ASTM D 2270
Viscosity, dynamic (CCS)	5380 cP	ASTM D 5293
Sulphated ash	0.89 wt%	ASTM D 874
Flash point	204 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

Article number E100145 Version 1.0, 25-03-2016