



Tractor oils - S.T.O.U.

Eurol Altrack 10W-40 STOU SYN

Universal semi-synthetic tractor oil for engine and transmission

Description

Eurol Altrack 10W-40 STOU Semi-synthetic is an universal, multi-grade tractor oil (Super Tractor Oil Universal). The product is recommended for modern tractors, requiring an optimum lubrication under the most severe operating conditions.

Eurol Altrack 10W-40 STOU Synthetic is especially developed for the lubrication and cooling of the engine, clutches, final drives, transmissions, and 'wet brakes'. The multifunctional character of the product prevents mistakes in the oil selection and reduces stock.

Eurol Altrack 10W-40 STOU Synthetic has a very strong dispersing and deterging capability. The high resistance against ageing, corrosion and foam building guarantees an excellent, reliable and long-lasting lubrication.

Performance level

- API CG-4/SF
- API GL-4
- Allison C-4
- ZF TE ML 06B/06C/06R/07B
- Case MS 1206, MS1209
- MB 228.1
- MAN 271
- ZF TE-ML 07D
- John Deere J21A
- Ford WSS-M2C159-B/C
- CNH MAT 3505
- CNH MAT 3525
- MF M1145
- MF M1144
- MF M1143
- MF M1139
- MF M1135
- Ford NH 82009201/2/3
- Ford WSS-M2C134-D
- John Deere J20C, J27
- NH 024 C
- NH 030 C
- NH 410 B
- NH 420 A
- Caterpillar TO-2

Recommended for use

• MIL-L-2105

Physical properties

| Colour | brown | |
|-------------------------------|------------|-------------|
| Density at 20°C | 0.868 kg/l | ASTM D 4052 |
| Viscosity, kinematic at 40°C | 98.7 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 14.6 cSt | ASTM D 445 |
| Viscosity Index | 153 | ASTM D 2270 |
| Viscosity, dynamic (CCS) | 6760 cP | ASTM D 5293 |
| Flash point | 199 °C | ASTM D 93 |
| Pour point | -42 °C | ASTM D 97 |

Article number E105082 Version 2.0, 27-03-2023