



Tractor oils - U.T.T.O.

## Eurol Hykrol JD 68

UTTO for agricultural transmissions, clutches, final drives and wet brakes

### Description

Eurol Hykrol JD 68 has been especially developed for transmissions of combined bulldozer, tractor and other agricultural devices, fluid clutches, power steering, hydraulic systems and torque converters.

Eurol Hykrol JD 68 has very favourable friction characteristics and is therefore exceptionally suited for "wet brake"- systems. It prevents so-called 'stick slip'.

Eurol Hykrol JD 68 has a high viscosity index, a very strong oil film and good EP- and anti-wearing properties. It offers good protection against corrosion, oxidation and foam building.

### Approved

- ZF TE-ML 03E
- ZF TE-ML 05F
- ZF TE-ML 17E
- ZF TE-ML 21F
- ZF registration no.001971

### Performance level

- API GL-4
- Allison C-4
- John Deere J20A, J20C
- Case MS 1206, MS 1207, MS 1210
- CNH MAT 3525
- FNHA-2-C-201.00
- MF M1145
- MF M1143
- MF M1141
- MF M1135
- Volvo WB 101
- ZF TE-ML 06K
- Ford WSS-M2C134-D
- Caterpillar TO-2

### Recommended for use

- Komatsu KES 07.866
- CNH MAT 3540
- AGCO POWERFLUID 821XL
- AGCO Q-1826 (Whitefarm)
- ARGO-IE-390
- HCE-102/102W
- JCB 4000/0500 – JCB 4000/2200
- Kubota UDT Fluid
- NH 410B/-434B/-540B
- SDFG OT 1891
- Valtra Transmission XT60+

### Physical properties

Colour	brown	
Density at 20°C	0.871 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	60.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.1 cSt	ASTM D 445
Viscosity Index	153	ASTM D 2270
Viscosity, dynamic (CCS)	3250 cP	ASTM D 5293
Flash point	210 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E105820  
Version 5.0, 21-03-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.