



Transmission oils - Fully Synthetic

Eurol MTF 75W-85 FE GL5

Fully synthetic gear oil with fuel-saving properties

Description

Eurol MTF 75W-85 FE GL5 is a fully synthetic fuel-saving transmission oil, which can be used in manual transmissions and final drives, for which GL-5 is required.

Eurol MTF 75W-85 FE GL5 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol MTF 75W-85 FE GL5 has an excellent high load carrying capacity for an excellent absorption of sudden peak loads. The viscosity decrease due to heavy loads is only slightly, which will extend oil drain intervals (and in some cases lifetime filling) and ensures proper viscosity.

Eurol MTF 75W-85 FE GL5 contains special friction modifiers, which ensure sustainable fuel saving and less heat development.

Eurol MTF 75W-85 FE GL5 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Eurol MTF 75W-85 FE GL5 is compatible with most elastomers and seal materials and does not foam under extreme loads.

Performance level

- API GL-5
- MB 235.7
- ZF TE-ML 18

Recommended for use

- VW G 055 190
- VW G 052 190
- VW G 052 145
- Fiat
- BMW
- Alfa Romeo
- LANCIA

Physical properties

Colour	amber	
Density at 20°C	0.87 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	81.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.1 cSt	ASTM D 445
Flash point	190 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

Article number E110081 Version 2.1, 21-07-2021