



Technical fluids - Powersteering

Eurol LDS Fluid

Especially for Citroën Hydractive III suspension units

Description

Eurol LDS Fluid is a synthetic hydraulic fluid, especially developed for power steering systems, levelling systems and hydraulic (suspension) systems. This specific product is recommended for the Citroën HYDRActive 3 system.

Eurol LDS Fluid has a very high viscosity index and a very low pour point. Therefore, the product is recommended for an optimum performance of power steering systems, also at very low ambient temperatures.

Eurol LDS Fluid protects the system against oxidation. Because of the high boiling point and the water resistance, the product can be applied for a long lasting and safe use when this type of product is prescribed.

The drain interval is 5 years or 200.000 km, depending on which situation occurs first.

Performance level

- DIN 51524/3 (HVLP)
- PSA S71 2710 (LDS)

Physical properties

| | | |
|-------------------------------|-------------|-------------|
| Colour | dark orange | |
| Density at 20°C | 0.826 kg/l | ASTM D 4052 |
| Viscosity, kinematic at 40°C | 18.8 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 6.5 cSt | ASTM D 445 |
| Flash point | 155 °C | ASTM D 93 |
| Pour point | -54 °C | ASTM D 97 |

Article number E113673
Version 1.1, 09-12-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.