



Eurol Fullsynt. Compr.olie 46

Fully synthetic compressor oil

Description

Eurol Full Synthetic Compressor oil ISO-VG 46 is based on full synthetic base stocks and has been specially developed for the lubrication of rotating oil cooled compressors (ISO-VG 46 and 68). Including the very critical hydrovane compressors, reciprocating compressors (ISO-VG 100) and vacuum pumps. This oil is applicable in a very broad temperature range (-20 tot 205°C) and has a good thermal and oxidation stability.

Eurol Full Synthetic Compressor oil ISO-VG 46 prevents wear and the build-up of sludge and carbon deposits. As a result, the drain intervals can be extended up to eight times the normal service life of conventional compressor oils.

Eurol Full Synthetic Compressor oil ISO-VG 46 offers good cooling and sealing abilities and is capable to demulsify water in a rapid way. Due to the limited evaporation of this oil, the oil consumption and the risk of thickening or deposit build-up are minimized.

Performance level

- DIN 51524/2 (HLP)
- SAE Ms1003-2
- DIN 51506: VDL
- GM LJ

Physical properties

Colour	amber	
Density at 20°C	0.852 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	48 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.1 cSt	ASTM D 445
Viscosity Index	141	ASTM D 2270
Flash point	228 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E118866
Version 3.2, 07-04-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.