



Industrial oils - Airlube oil

Eurol Eurax EP ISO-VG 46

Lubricant for pneumatic tools

Description

Eurol Eurax EP is a specially formulated industrial fluid, based on high performance base oils and selected additives for the lubrication of pneumatic tools.

Eurol Eurax EP has a high viscosity index, providing an excellent lubrication under both low and high operating temperatures and loads. It disperses water and lowers the friction coefficient in particular under boundary lubrication conditions.

Eurol Eurax EP has been formulated with anti-wear and EP additives for optimum protection. Extreme Pressure additives will absorb high peak loads that can occur in pneumatic driven tools. The dedicated additive package prevents rust and corrosion in wet conditions.

Physical properties

| | | |
|-------------------------------|------------|-------------|
| Colour | Yellow | |
| Density at 20°C | 0.858 kg/l | ASTM D 4052 |
| Viscosity, kinematic at 40°C | 46 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 7.7 cSt | ASTM D 445 |
| Viscosity Index | 136 | ASTM D 2270 |
| Flash point | 202 °C | ASTM D 93 |
| Pour point | -30 °C | ASTM D 97 |

Article number E119850
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.