



Transmission oils - Mineral

Eurol Universal Gear Oil

Gearbox oils for most occurring mopeds

Description

Eurol Gearbox Oil is a series of special oils for perfect lubrication of the most occurring mopeds.

Eurol Gearbox oils ensure uncomplicated shifting of straight or bevel geared transmissions.

Eurol Gearbox oils have a high viscosity index, ensuring an optimum protection under both low and high temperature conditions.

Performance level

- DIN 51524/2 (HLP)
- U.S. Steel 127
- U.S. Steel 126
- Sperry Vickers I-286-S
- AFNOR NF E 48-603 HM
- AFNOR NF E 48-603 HL
- DIN 51524/1 (HL)

Physical properties

Colour	amber	
Density at 20°C	0.875 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	103.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.5 cSt	ASTM D 445
Viscosity Index	98	ASTM D 2270
Flash point	260 °C	ASTM D 93
Pour point	-27 °C	ASTM D 97

Article number E126105
Version 1.2, 11-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.