



Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C BS 6580

Meets BS 6580 standard, suitable for open and closed cooling systems

Description

Eurol Coolant -36 has especially been developed for open and closed cooling systems, according to modern requirements of the European car manufacturers. This coolant can also be used for heat transfer systems and central heating installations.

Eurol Coolant -36 prevents from scale formation, corrosion, foam-building, sludge formation and leakage. The product does not affect rubber, plastics, metals, aluminum or its alloys.

Eurol Coolant -36 provides a permanent, guaranteed protection against freezing up to -36 °C and has to be used undiluted. Never top-up with water.

Eurol Coolant -36 is nitrite, amine and phosphate free.

Performance level

- BS 6580
- ASTM D3306

Physical properties

Colour	Blue	
Density at 20°C	1.064 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177
pH	8.6	

Article number E504105
Version 1.1, 04-01-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.