



Greases

# Eurol Universal Lithium Grease EP 2

Universal lithium grease for various applications

## Description

Eurol Universal Lithium Grease EP 2 is a high performance, all-purpose grease with EP additives (without heavy metals) and a good pumpability. It offers an excellent corrosion protection and has very good anti-oxidation properties.

Eurol Universal Lithium Grease EP 2 is extremely suitable for high working temperature conditions, heavy loads, shock loads and where water and dirt may penetrate the greasing point.

Eurol Universal Lithium Grease EP 2 guarantees optimum protection, also under heavy working conditions, extending equipment life-time and reducing maintenance costs.

Eurol Universal Lithium Grease EP 3 is recommended for application in hot/ tropical conditions.

## Performance level

- DIN 51825: KP2.5K-20
- ISO-L-XBCHB2.5

## Physical properties

Colour	dark brown	
Density at 20°C	0.91 kg/l	ASTM D 4052
NLGI consistency	2-3	
Thickener type	Lithium	
Base oil type	Mineral	
Base oil viscosity	290 cSt	ASTM D 445
4-ball weld load	260 kg	ASTM D 2596
Operating temperature	-20 – 130 °C	
Dropping point	185 °C	

Article number E901030  
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.