



Greases

Eurol Graphite Grease

Graphite based multi-purpose grease

Description

Eurol Graphite Grease is an easily pumpable lubricating grease. The present graphite will form a lubricating film onto the surface, which has an operating temperature up till 500°C. The oil, which is also present in the grease will be evaporated at this elevated temperatures, but the graphite will provide the required lubrication. The grease will give excellent protection against corrosion and oxidation.

Eurol Graphite Grease can be used at high temperatures, high pressures, variations in forces and in places where water and dirt can easily be picked up.

Eurol Graphite Grease can be applied in bearings of oven conveyor-belts, plungers of hydraulic pumps and guide bearings of rollers. The grease can also be applied on packing seals of flanges and for chutes, which are used in a smithy or lumberyard.

Performance level

- DIN KFP2K-30
- ISO-L-XCCFB 2

Physical properties

Colour	Black	
Density at 20°C	0.92 kg/l	ASTM D 4052
NLGI consistency	2	
Thickener type	Lithium	
Base oil type	Mineral	
Base oil viscosity	110 cSt	ASTM D 445
4-ball weld load	240 kg	ASTM D 2596
Operating temperature	-30 – 130 °C	
Dropping point	180 °C	

Article number E901072
Version 1.0, 13-12-2018

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.