



Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 02.05.2014 Revision date: 06.12.2023 Supersedes: 29.08.2023 Version: 5.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Eurol Coolant -36°C GLX
UFI : GX6Q-R6DF-370E-JKY6
Product code : E504144
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, professional use, Consumer use
Function or use category : Anti-freezing agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol B.V.
Energiestraat 12
NL-7442 DA Nijverdal
The Netherlands
Tel: +31 548 615 165
reach@eurol.com - www.eurol.com

1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Repeated exposure, Category 2 H373

Full text of H- and EUH-statements: see section 16

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

May cause damage to organs through prolonged or repeated exposure. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

CLP Signal word

: Warning

Contains

: potassium 3,5,5-trimethylhexanoate; ethane-1,2-diol

Hazard statements (CLP)

: H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Child-resistant fastening

: Not applicable

Tactile warning

: Applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanediol; ethylene glycol substance with national workplace exposure limit(s) (GB, IE, MT); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816- 28	35 – 50	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 2, H373
potassium 3,5,5-trimethylhexanoate	CAS-No.: 93918-10-6 EC-No.: 299-890-3 REACH-no: 01-2120747787- 36	1 – 3	Acute Tox. 4 (Oral), H302 (ATE=1160 mg/kg bodyweight) Skin Corr. 1, H314 Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

Euroil Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Bad taste. Damage to kidneys. The main component of this product is harmful by ingestion. Swallowing a small quantity of this material will result in serious health hazard.
Symptoms/effects upon intravenous administration	: Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustion generates: CO, CO ₂ .
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Use protective clothing.
Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Emergency procedures : No specific measures are necessary.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.
Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible products : Reacts vigorously with strong oxidizers and acids.
Maximum storage period : 5 year
Storage temperature : ≤ 40 °C
Information on mixed storage : Keep away from : Oxidizing materials. Strong acids.
Storage area : Store at ambient temperature.
Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethanediol; ethylene glycol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOELV TWA (mg/m ³)	52 mg/m ³
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m ³)	104 mg/m ³
IOELV STEL (ppm)	40 ppm
Notes	Skin

Eurool Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanediol; ethylene glycol (107-21-1)	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Ethane-1,2-diol [Ethylene glycol]
OEL (8 hours ref) (mg/m ³)	10 mg/m ³ particulate 52 mg/m ³ vapour
OEL (8 hours ref) (ppm)	20 ppm vapour
OEL (15 min ref) (mg/m ³)	104 mg/m ³ vapour
OEL (15 min ref) (ppm)	40 ppm vapour
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Malta - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA (mg/m ³)	52 mg/m ³
OEL TWA (ppm)	20 ppm
OEL STEL (mg/m ³)	104 mg/m ³
OEL STEL (ppm)	40 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (mg/m ³)	10 mg/m ³ particulate 52 mg/m ³ vapour
WEL TWA (ppm)	20 ppm vapour
WEL STEL (mg/m ³)	104 mg/m ³ vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0.4		EN ISO 374
Disposable gloves	Butyl rubber	6 (> 480 minutes)	0.7		EN ISO 374

Other skin protection

Materials for protective clothing:

Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Neoprene or nitrile rubber gloves. Butylrubber protective gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: pink.
Appearance	: Liquid.
Odour	: odourless.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -36 °C

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Boiling point	: > 100 °C
Flammability (solid, gas)	: Non flammable.
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 111 °C ASTM D 93
Auto-ignition temperature	: > 390 °C
Decomposition temperature	: Not available
pH	: 8,4
pH solution	: 7 – 10
Viscosity, kinematic	: Not available
Solubility	: Miscible with water.
Log Kow	: Not available
Log Pow	: < -0,1
Vapour Pressure 20°C	: < 2 hPa
Vapour pressure at 50°C	: Not available
Density	: 1,06 – 1,07 kg/l ASTM D 4052
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air=1)
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1)	: < 0,1
Other properties	: Gas/vapour heavier than air at 20°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

CO, CO₂.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Eurol Coolant -36°C GLX

ATE CLP (oral)	1016,973 mg/kg bodyweight
----------------	---------------------------

potassium 3,5,5-trimethylhexanoate (93918-10-6)

LD50 oral rat	1160 mg/kg
---------------	------------

ethanediol; ethylene glycol (107-21-1)

LD50 oral rat	7712 mg/kg bodyweight Animal: rat
---------------	-----------------------------------

LD50 dermal	> 3500 mg/kg mouse
-------------	--------------------

LC50 Inhalation - Rat	> 2,5 mg/l (6h)
-----------------------	-----------------

Skin corrosion/irritation : Causes skin irritation.
pH: 8,4

ethanediol; ethylene glycol (107-21-1)

pH	6 – 7,5
----	---------

Serious eye damage/irritation : Causes serious eye irritation.
pH: 8,4

ethanediol; ethylene glycol (107-21-1)

pH	6 – 7,5
----	---------

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

ethanediol; ethylene glycol (107-21-1)

STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
------------------------	---

Aspiration hazard : Not classified

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

potassium 3,5,5-trimethylhexanoate (93918-10-6)

EC50 72h - Algae [1]	189,87 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
----------------------	---

NOEC chronic crustacea	≥ 100 mg/l Daphnia magna (Water flea)
------------------------	---------------------------------------

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanediol; ethylene glycol (107-21-1)	
LC50 fish 1	> 72860 mg/l Test organisms (species): Pimephales promelas
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic fish	15380 mg/l Pimephales promelas
NOEC chronic crustacea	8590 mg/l daphnia

12.2. Persistence and degradability

ethanediol; ethylene glycol (107-21-1)	
Persistence and degradability	Readily biodegradable in water. easily degradable in the soil.
Biochemical oxygen demand (BOD)	0,47 g O ₂ /g substance
Chemical oxygen demand (COD)	1,24 g O ₂ /g substance
ThOD	1,29 g O ₂ /g substance
BOD (% of ThOD)	0,36

12.3. Bioaccumulative potential

Eurol Coolant -36°C GLX	
Log Pow	< -0,1

ethanediol; ethylene glycol (107-21-1)	
Log Pow	-1,36
Bioaccumulative potential	No bioaccumulation.

12.4. Mobility in soil

ethanediol; ethylene glycol (107-21-1)	
Surface tension	0,048 N/m (20 °C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.

Eurol Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Ecology - waste materials : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
- European List of Waste (LoW, EC 2000/532) : 16 01 14* - antifreeze fluids containing dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

EuroL Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	EuroL Coolant -36°C GLX ; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) ; potassium 3,5,5-trimethylhexanoate ; ethanediol; ethylene glycol
3(c)	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SECTION 2. SECTION 3.

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

EuroI Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

EuroI Coolant -36°C GLX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
Skin Corr. 1	Skin corrosion/irritation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT RE 2	H373	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.