



Motorcycle oils 4T - Mineral

Eurol Sport Touring 10W-40

Mineral motor oil for 4-stroke motorcycles

Description

Eurol Sport Touring 10W-40 is a mineral engine oil without friction modifiers, especially developed for 4-stroke motorcycles. This oil also can be applied in motorcycle transmissions where an API SF or SG oil is prescribed.

Eurol Sport Touring 10W-40 is suitable for touring, racing and cross applications and contains a dedicated ester technology giving optimized friction characteristics and provides an excellent protection against wear, deposits, sludge and oxidation under all conditions.

Even under the most severe operating conditions, air-absorption and foam building are prevented.

Eurol Sport Touring 10W-40 has a very low volatility, reducing oil thickening and oil consumption to a minimum. Due to the sophisticated formulation, this oil offers excellent protection to gearboxes and wet disc clutches and prevents from slippery and sticking clutches.

Despite the high loads between the gears, the special oil thickener hardly breaks down, so that at high temperatures the viscosity stays in grade to assure a strong lubricant film.

At low temperatures Eurol Sport Touring 10W-40 rapidly builds up a stable lubricant film for an optimum protection at the cold start.

Performance level

- API SL/CF
- JASO MA
- JASO MA2

Physical properties

Colour	brown	
Density at 20°C	0.87 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	105 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.9 cSt	ASTM D 445
Viscosity Index	147	ASTM D 2270
Viscosity, dynamic (CCS)	6463 cP	ASTM D 5293
Base number	8.4 mg	ASTM D 2896
Sulphated ash	1.18 wt%	ASTM D 874
Flash point	205 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Article number E100011
Version 3.0, 05-03-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.