



Industrial oils - Slideway oil

## Eurol Slideway Oil 68

High performance lubricant for metal and plastic slideways

### Description

Eurol Slideway Oil 68 is a series of new zinc free high performance oils, recommended for the lubrication of both metal, as well as plastic slideways.

Eurol Slideway Oil 68 provides excellent friction characteristics and lubricity, eliminating 'stick-slip'. Because of this, a very good surface finish can be achieved, with less production rejects.

Eurol Slideway Oil 68 has excellent demulsifying properties and will not drip, which extends the lifetime of both the slideway oil, as well as the cutting fluid. Oxidation and corrosion inhibitors keep the oil and the machine tool in a perfect condition.

Besides an excellent protection against corrosion, Eurol Slideway Oil 68 also offers a strong and stable lubricant film.

Eurol Slideway Oil 68 can also be used in hydraulic systems, as a chain oil in circulating lubrication systems and for the lubrication of conveyor belts.

### Performance level

- DIN 51524/2 (HLP)
- Cincinnati Machine P-47
- GM LS-2
- DIN 51 502 CGLP

### Physical properties

Colour	amber	
Density at 20°C	0.865 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	67.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.4 cSt	ASTM D 445
Viscosity Index	117	ASTM D 2270
Flash point	184 °C	ASTM D 93
Pour point	-9 °C	ASTM D 97

Article number E121490  
Version 2.1, 08-08-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.