



Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C GLX PP

Silicate-bearing long-life coolant VW-TL 774 G

Description

Eurol Coolant -36 GLX PP was specially developed for the new generation cooling systems of V.A.G. Eurol Coolant -36 GLX PP is based on ethylene glycol and is approved for Volkswagen norm TL 774 G.

Eurol Coolant -36 GLX PP can be used in all Volkswagens starting with 09-2006 models, as well as in all VW Phaeton/Touareg and Audi A8 / Q7.

Eurol Coolant -36 GLX PP protects the cooling system from freezing down to temperatures of -36°C, and contains environmentally-friendly additives.

Eurol Coolant -36 GLX PP contains silicate. This technology is known under the name LOBRID.

It can safely be added to Coolant G12+ (TL 774 F), the other way round is however strongly discouraged.

Eurol Coolant -36 GLX PP must be used undiluted; never add water.

Performance level

- VW TL-774 G (G12++)
- MAN 324 Typ Si-OAT
- DTFR 29D120 (MB 326.5)

Recommended for use

- Scania TB 1451

Physical properties

Colour	pink	
Density at 20°C	1.073 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177
pH	8.3	

Article number E504148
Version 1.2, 21-03-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.