



Technical fluids - Brakefluids

Eurol Brake Fluid DOT 5 Silic

Silicone-based brake fluid for old-timers / go-karts / Harley Davidson

Description

Eurol Brake Fluid DOT 5 Silicone is a silicone-based brake fluid. The product has a broad temperature range (-55°C up to +260°C) and ensures optimum performance at low temperatures and a low toxicity.

Eurol Brake Fluid DOT 5 Silicone helps to prevent corrosion and provides excellent lubrication to rubber seals and metals. It extends brake system life-cycle and will not affect paints.

Eurol Brake Fluid DOT 5 Silicone can safely be used in hydraulic brake and clutch systems of cars, (racing) motorcycles, Harley Davidson bikes, go-karts, old-timers and in industrial applications.

NB: The old brake fluid has to be drained thoroughly from the system before re-fill.

Eurol Brake Fluid DOT 5 Silicone should never be mixed with other brake fluids.

Eurol Brake Fluid DOT 5 Silicone is not suitable for Citroën cars.

Performance level

- FMVSS 116 DOT 5
- MIL-PRF-46176B

Physical properties

Colour	Purple	
Density at 20°C	0.95 kg/l	ASTM D 4052
Viscosity, kinematic at 100°C	13.9 cSt	ASTM D 445
Flash point	150 °C	ASTM D 93

Article number E801550
Version 1.1, 08-01-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.