



Passenger car engine oils - Mineral

Eurol Special 10W-30

Mineral motor oil for gasoline, LPG and diesel engines

Description

Eurol Special Multigrades are motor oils, formulated with shear-stable viscosity improvers to prevent viscosity drops after some time. Because of this, a strong and stable lubricant film is guaranteed, even at high temperatures.

Eurol Special Multigrades contain deterging and dispersing additives, keeping the oil and the engine clean, even the most critical parts. Corrosion and sludge are reduced to a minimum, while anti-wear additives, together with the high quality base oils, offer maximum protection to heavily loaded parts. Eurol Special Multigrades have a long life-time and assure a low oil consumption. This oil can be used in all gasoline and LPG engines, as well in light duty, non-turbo charged diesel engines.

Eurol Special Multigrades are especially suitable for older cars as running-in motor oil.

Performance level

• API SF/CD

Recommended for use

- MIL-L-2104D
- MIL-L-46152C

Physical properties

i ilyolodi proportioo		
Colour	brown	
Density at 20°C	0.852 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	68.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.9 cSt	ASTM D 445
Viscosity Index	149	ASTM D 2270
Viscosity, dynamic (CCS)	3619 cP	ASTM D 5293
Base number	8.0 mg	ASTM D 2896
Sulphated ash	1.2 wt%	ASTM D 874
Flash point	218 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E100060 Version 2.2, 17-09-2020