



Passenger car engine oils - Fully Synthetic

Eurol Syntence LV 0W-20

VW 508.00/509.00 "blue" oil for specific engines of Volkswagen Group

Description

Eurol Syntence LV 0W-20 is a longlife PAO-based oil formulation with a universal applicability in gasoline and diesel engines for specific Volkswagen, Audi, Skoda, Seat vehicles requiring the VW 508.00/509.00 specification.

Eurol Syntence LV 0W-20 is having green coloring (not "blue") and Zirconium marker. These properties are mandatory for a VW reblend approval.

Eurol Syntence LV 0W-20 enables the engine to perform under severe driving conditions (motorway and urban traffic) due to its special additive package. Also improved fuel economy (> 4% benefit when compared to a SAE 15W-40 reference oil) and exhaust emission reduction can be obtained with this product. Because of the unique formulation, the oil has a low evaporation tendency, minimizing oil consumption.

Eurol Syntence LV 0W-20 is going to be formally approved for the VW 508.00/509.00 specification, along with the first fill specification VW TL 52577. Only the two VW specifications are valid on this 0W-20 formulation, although the Porsche C20 specification may be implemented as compatible. Eurol Syntence LV 0W-20 is not backward compatible with the earlier Volkswagen specifications required in certain versions of the older engines.

Eurol Syntence LV 0W-20 is recommended for the new EA888 Gen III 2.0 TFSI 140 KW, VW 1.5 TSI 96 KW/110KW and EA897 Gen I 3.0 TDI CR 160 KW Volkswagen/Audi engines. It is expected that 15 to 20 new "blue" oil capable engines types will be introduced in the near future, representing 50% of total VW production, including Audi, Skoda and Seat brands.

Approved

- VW 508.00 / 509.00

Performance level

- ACEA C5
- Porsche C20

Recommended for use

- Ford WSS-M2C956-A1

Physical properties

Colour	Green	
Density at 20°C	0.834 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	42.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.1 cSt	ASTM D 445
Viscosity Index	168	ASTM D 2270
Viscosity, dynamic (CCS)	5300 cP	ASTM D 5293
HTHS	2.6 cP	CEC CL 23
Base number	8.3 mg	ASTM D 2896
Sulphated ash	0.8 wt%	ASTM D 874
Flash point	230 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Article number E100159
Version 7.0, 07-02-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.