



Eurol Transyn 75W-90 GL 4/5

Semi-synthetic transmission oil for manual gearboxes and final drives

Description

Eurol Transyn 75W-90 GL4/5 is a semi-synthetic, universal transmission/gear oil which can be applied in both manual gearboxes as well as in final drives, where an API GL-4 or 5 quality oil is prescribed. By this, the product can reduce the stock of transmission/gear oils.

Eurol Transyn 75W-90 GL4/5 can be used for the complete drive line. The product contains special additives reducing fuel consumption and eliminating shifting problems. Due to this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures the oil is protected against thermal oxidation.

Eurol Transyn 75W-90 GL4/5 can be used in synchromesh gearboxes and ensures easy and smooth shifting, even at low temperatures.

Eurol Transyn 75W-90 GL4/5 shows excellent EP (Extreme Pressure) characteristics to cope with heavy loads and vibrations. Viscosity drop, caused by heavy loads, is minimal so that this oil guarantees the right viscosity, even at prolonged drain intervals

Performance level

- API GL 4/5
- API MT-1
- MIL-L-2105 B/C/D
- ZF TE-ML 02B/05A/07A/08A/12E/16B/16C/16D/17B/19B/21A
- Mack GO-J
- MIL-PRF-2105E
- Volvo 97310
- Scania STO 1:0
- DAF
- MAN M 3343 Typ M
- MAN 342 Type M2
- MAN 341 Typ Z2

Recommended for use

- DTFR 13B100 (MB 235.1)
- DTFR 12B100 (MB 235.0)
- Arvin Meritor 076-N
- IVECO

Physical properties

Colour	amber	
Density at 20°C	0.883 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	86.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15 cSt	ASTM D 445
Viscosity Index	183	ASTM D 2270
Flash point	200 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

Article number E110075
Version 2.4, 18-10-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.