



Quality is in our nature

Greases - Aerosols

Eurol Ceramic Grease spray 400ML

Assembly paste spray for protection of wire connections

Description

Eurol Ceramic Grease Spray contains an assembly paste, consisting of finely divided ceramic particles in a fusible beryllium based grease. There are extra anticorrosion and antioxidation inhibitors added.

Eurol Ceramic Grease Spray does not contain any metals and is suitable for parts that are exposed to high temperatures and/or high workload, such as ABS, ASR and ESP systems, lambda sensors and exhaust parts.

Eurol Ceramic Grease Spray provides a fast and easy loosening of wire connections, gaskets and packings. Even after long exposure to high temperatures up to 1000°C, corrosive atmospheres or high loads, quick and easy assembly of wire connections.

Eurol Ceramic Grease Spray must be shaken well before use. Spray at approx. 20 cm from the object. Apply the desired quantity.

Use Eurol Ceramic Grease Spray only in well ventilated

areas. In case of eye contact immediately rinse eyes with plenty of water. Flammable substance.

Eurol Ceramic Grease Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

Physical properties

| | | |
|-------------|--------|-----------|
| Flash point | -18 °C | ASTM D 93 |
|-------------|--------|-----------|

E701123

Version 1.0, 16-02-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com